

PART 70 MINOR SOURCE MODIFICATION OFFICE OF AIR QUALITY

**Monaco Coach Corporation
1205 East Lincoln Street
Nappanee, Indiana 46550**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Source Modification No.: 039-15249-00087	
Issued by: Original signed by Paul Dubenezky Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: May 9, 2002

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]
- A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONSTRUCTION CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Effective Date of the Permit [IC13-15-5-3]
- B.3 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

C GENERAL OPERATION CONDITIONS

- C.1 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]
- C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]
- C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]
- C.4 Opacity [326 IAC 5-1]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Compliance Requirements [326 IAC 2-1.1-11]
- C.8 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.9 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]
- C.10 Compliance Response Plan - Preparation, Implementation, Records, and Reports
- C.11 Emergency Provisions
- C.12 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
- C.13 General Record Keeping Requirements [326 IAC 2-7-5(3)]
- C.14 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

D.1 FACILITY OPERATION CONDITIONS - Woodworking Operations controlled by baghouses DC48-03 and DC48-04

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Particulate Matter (PM) [326 IAC 6-3-2]
- D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Determination Requirements

- D.1.3 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

- D.1.4 Visible Emissions Notations
- D.1.5 Baghouse Inspections
- D.1.6 Broken or Failed Bag Detection

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- D.1.7 Record Keeping Requirements

Certification
Affidavit

SECTION A

SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

The Permittee owns and operates a stationary wood furniture and fiberglass panel manufacturing plant.

Responsible Official:	Richard E. Bond, Vice President
Source Address:	1205 East Lincoln Street, Nappanee, Indiana 46550
Mailing Address:	P.O. Box 465, Wakarusa, Indiana 46573
General Source Phone Number:	219-862-7347
SIC Code:	2431
County Location:	Elkhart
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Part 70 Permit Program Minor Source, under PSD Rules; Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

This stationary source is approved to construct and operate the following emission units and pollution control devices:

- (a) Woodworking Operations controlled by:
 - (1) one (1) baghouse for particulate control, identified as DC48-03, controlling woodworking equipment with a maximum throughput capacity of 5000 pounds per hour, and exhausting at stack DC48-03.
 - (2) one (1) baghouse for particulate control, identified as DC48-04, controlling woodworking equipment with a maximum capacity of 3000 pounds per hour, and exhausting at stack DC48-04.

A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because:

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

SECTION B GENERAL CONSTRUCTION CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Effective Date of the Permit [IC13-15-5-3]

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

B.3 Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

SECTION C GENERAL OPERATION CONDITIONS

C.1 Certification [326 IAC 2-7-4(f)][326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) when operation begins, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The PMP and the PMP extension notification do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

(a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

C.4 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment is are in operation.

Compliance Requirements [326 IAC 2-1.1-11]

C.7 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.8 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

If required by Section D, all monitoring and record keeping requirements shall be implemented when operation begins. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

C.9 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.10 Compliance Response Plan - Preparation, Implementation, Records, and Reports[326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
- (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (4) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (5) Failure to take reasonable response steps shall constitute a violation of the permit.

- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.11 Emergency Provisions [326 IAC 2-7-16]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and IDEM Northern Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality,
Compliance Section), or
Telephone Number: 317-233-5674 (ask for Compliance Section)
Facsimile Number: 317-233-5967

and

Telephone Number: 219-245-4870 (Northern Regional Office)
Facsimile Number: 219-245-4877

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
 - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
 - (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(10) be revised in response to an emergency.
 - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
 - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

**C.12 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]
[326 IAC 2-7-6]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

C.13 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.14 General Reporting Requirements [326 IAC 2-7-5(3)(C)]

- (a) The reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (d) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

SECTION D.1 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]

- (a) Woodworking Operations controlled by:
- (1) one (1) baghouse for particulate control, identified as DC48-03, controlling woodworking equipment with a maximum throughput capacity of 5000 pounds per hour, and exhausting at stack DC48-03.
 - (2) one (1) baghouse for particulate control, identified as DC48-04, controlling woodworking equipment with a maximum capacity of 3000 pounds per hour, and exhausting at stack DC48-04.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Particulate Matter (PM) [326 IAC 6-3-2]

- (a) Pursuant to 326 IAC 6-3-2 (Process Operations), the allowable PM emission rate from the woodworking facilities controlled by the baghouse identified as DC48-03 shall not exceed 7.58 pounds per hour when operating at a process weight rate of 5000 pounds per hour.
- (b) Pursuant to 326 IAC 6-3-2 (Process Operations), the allowable PM emission rate from the woodworking facilities controlled by the baghouse identified as DC48-04 shall not exceed 5.38 pounds per hour when operating at a process weight rate of 3000 pounds per hour.

The pounds per hour limitations was calculated with the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.2 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

Compliance Determination Requirements

D.1.3 Particulate Matter (PM)

In order to comply with D.1.1, the baghouses DC48-03 and DC48-04 for PM control shall be in operation and control emissions from the associated woodworking operations at all times that the associated woodworking operations are in operation.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.4 Visible Emissions Notations

- (a) Daily visible emission notations of the woodworking operation stack exhausts (DC48-03 and DC48-04) shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.1.5 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the woodworking operation when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.

D.1.6 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.7 Record Keeping Requirements

- (a) To document compliance with Condition D.1.4, the Permittee shall maintain daily records of visible emission notations of the woodworking operation stack exhausts (DC48-03 and DC48-04).
- (b) To document compliance with Condition D.1.5, the Permittee shall maintain records of the results of the inspections required under Condition D.1.5 and the dates the vents are redirected.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

PART 70 SOURCE MODIFICATION CERTIFICATION

Source Name: Monaco Coach Corporation
Source Address: 1205 East Lincoln Street, Nappanee, Indiana 46550
Mailing Address: P.O. Box 465, Wakarusa, Indiana 46573
Source Modification No.: 039-15249-00087

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this approval.

Please check what document is being certified:

- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Affidavit (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

Mail to: Permit Administration & Development Section
Office Of Air Quality
100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015

Monaco Coach Corporation
P.O. Box 465
Wakarusa, Indiana 46573

Affidavit of Construction

I, _____, being duly sworn upon my oath, depose and say:
(Name of the Authorized Representative)

1. I live in _____ County, Indiana and being of sound mind and over twenty-one (21) years of age, I am competent to give this affidavit.

2. I hold the position of _____ for _____.
(Title) (Company Name)

3. By virtue of my position with _____, I have personal
(Company Name)

knowledge of the representations contained in this affidavit and am authorized to make these representations on behalf of _____.
(Company Name)

4. I hereby certify that Monaco Coach Corporation, 1205 East Lincoln Street, Nappanee, Indiana 46550, has constructed the woodworking operations controlled by baghouses DC48-03 and DC48-04 in conformity with the requirements and intent of the construction permit application received by the Office of Air Quality on December 3, 2001 and as permitted pursuant to **Source Modification No. 039-15249-00087** issued on _____.

Further Affiant said not.

I affirm under penalties of perjury that the representations contained in this affidavit are true, to the best of my information and belief.

Signature

Date

STATE OF INDIANA)
)SS

COUNTY OF _____)

Subscribed and sworn to me, a notary public in and for _____ County and State of Indiana on this _____ day of _____, 20 _____.

My Commission expires: _____

Signature

Name (typed or printed)

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Source Modification to a Part 70 Source

Source Background and Description

Source Name:	Monaco Coach Corporation
Source Location:	1205 East Lincoln Street, Nappanee, Indiana 46550
County:	Elkhart
SIC Code:	2431
Operation Permit No.:	T039-6116-00087
Operation Permit Issuance Date:	Pending
Source Modification No.:	039-15249-00087
Permit Reviewer:	Trish Earls/EVP

The Office of Air Quality (OAQ) has reviewed a modification application from Monaco Coach Corporation relating to the operation of a stationary wood furniture and fiberglass panel manufacturing plant.

History

On December 3, 2001, Monaco Coach Corporation submitted an application to the OAQ requesting to add additional woodworking operations controlled by two (2) baghouses, identified as DC48-03 and DC48-04 to their existing plant. The woodworking operations were recently purchased from another company. These baghouses began operation for Monaco Coach Corporation in November and December of 2001, respectively. The baghouses will control emissions from the new woodworking equipment and equipment that will be relocated from the existing woodworking operations in Plant 42. The cyclone that is in Plant 42 will be left in place although no current activities are planned in this facility. Monaco Coach Corporation applied for a Part 70 permit on June 11, 1996 that is still pending with OAQ.

Unpermitted Emission Units and Pollution Control Equipment

The source also consists of the following unpermitted facilities/units:

- (a) Woodworking Operations controlled by:
 - (1) one (1) baghouse for particulate control, identified as DC48-03, controlling woodworking equipment with a maximum throughput capacity of 5000 pounds per hour, and exhausting at stack DC48-03.
 - (2) one (1) baghouse for particulate control, identified as DC48-04, controlling woodworking equipment with a maximum capacity of 3000 pounds per hour, and exhausting at stack DC48-04.

Existing Approvals

The source applied for a Part 70 Operating Permit (T039-6116-00087) on June 11, 1996. The source has been operating under previous approvals including, but not limited to, the following:

- (a) CP 039-10442-00087, issued on April 21, 1999;
- (b) CP 039-10299-00087, issued on February 5, 1999;
- (c) CP 039-1996-00087, issued on July 19, 1991;
- (d) PC (20) 1730, issued on February 21, 1989; and
- (e) Exemption, issued on March 4, 1987.

Enforcement Issue

- (a) IDEM is aware that equipment has been constructed and operated prior to receipt of the proper permit. The subject equipment is listed in this Technical Support Document under the condition entitled *Unpermitted Emission Units and Pollution Control Equipment*.
- (b) IDEM is reviewing this matter and will take appropriate action. This proposed permit is intended to satisfy the requirements of the construction permit rules.

Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
DC48-03	Baghouse DC48-03	30	2.5	22,500	ambient
DC48-04	Baghouse DC48-04	30	2.5	13,500	ambient

Recommendation

The staff recommends to the Commissioner that the Minor Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on December 3, 2001. Additional information was received on March 28, 2002.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (1 page).

Potential To Emit Before Controls (Modification)

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

Pollutant	Potential To Emit (tons/year)
PM	1,344.8
PM-10	1,344.8
SO ₂	0.0
VOC	0.0
CO	0.0
NO _x	0.0

There are no HAP emissions from this modification.

Justification for Modification

The Title V permit is being modified through a Minor Source Modification. Pursuant to 326 IAC 2-7-10.5(d)(9), the Part 70 source is being modified through a Minor Source Modification because the modification consists of the addition of woodworking equipment with baghouses for particulate matter control, which are of the same type as the existing permitted woodworking equipment, and which will comply with the same applicable requirements and permit terms and conditions as the existing woodworking equipment.

County Attainment Status

The source is located in Elkhart County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	maintenance attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Elkhart County has been designated as maintenance attainment or unclassifiable for ozone.

Source Status

Existing Source PSD Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	<250
PM-10	<250
SO ₂	<100
VOC	<250
CO	<100
NO _x	<100

- (a) This existing source is not a major stationary source because no attainment regulated pollutant is emitted at a rate of 250 tons per year or more, and it is not one of the 28 listed source categories.
- (b) These emissions are based upon the Title V draft permit (T039-6116-00087) still pending with the OAQ.

Potential to Emit After Controls for the Modification

The table below summarizes the total potential to emit, reflecting all limits, of the significant emission units for the modification.

	Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO ₂	VOC	CO	NO _x	HAPs
Baghouse DC48-03	8.44	8.44	0.0	0.0	0.0	0.0	0.0
Baghouse DC48-04	5.01	5.01	0.0	0.0	0.0	0.0	0.0
Total Emissions	13.45	13.45	0.0	0.0	0.0	0.0	0.0

This modification to an existing minor stationary source is not major because the emission increase is less than the PSD significant levels. Therefore, pursuant to 326 IAC 2-2 and 40 CFR 52.21, the PSD requirements do not apply.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this modification.

State Rule Applicability - Entire Source

326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

This source is not subject to the requirements of this rule. Pursuant to PC (20) 1730, issued on February 21, 1989, source-wide VOC emissions from this source were limited to less than 100 tons per year, making this a PSD minor source. At the time the previous construction permit was written, Elkhart County was designated as nonattainment for ozone. In 1994, Elkhart County was redesignated to attainment. Therefore, this limit will be revised in the Title V permit, pending with the OAQ, so that VOC emissions are limited to less than 250 tons per year rather than 100 tons per year. Since the emissions increase associated with this modification is less than the PSD significant modification thresholds of 250 tons per year, the requirements of this rule do not apply.

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting), because it is located in Elkhart County and has the potential to emit more than ten (10) tons per year of VOC. Pursuant to this rule, the owner/operator of the source must annually submit an emission statement for the source. The annual statement must be received by April 15 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8)(Emission Statement Operating Year).

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Exemptions), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 6-3-2 (Process Operations)

- (a) The particulate matter (PM) from the woodworking operations controlled by the baghouse identified as DC48-03 shall not exceed 7.58 pounds per hour when operating at a process weight rate of 5000 pounds per hour.
- (b) The particulate matter (PM) from the woodworking operations controlled by the baghouse identified as DC48-04 shall not exceed 5.38 pounds per hour when operating at a process weight rate of 3000 pounds per hour.

The limitations in paragraphs (a) and (b) above were calculated using the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

The baghouses shall be in operation at all times the associated woodworking equipment is in operation, in order to comply with this limit.

Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this modification are as follows:

1. The woodworking operations have applicable compliance monitoring conditions as specified below:
 - (a) Daily visible emissions notations of the woodworking operation stack exhausts (DC48-03 and DC48-04) shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee will record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Preventive Maintenance Plan for this unit shall contain troubleshooting contingency and corrective actions for when an abnormal emission is observed.
 - (b) An inspection shall be performed each calendar quarter of all bags controlling the woodworking operation when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors. All defective bags shall be replaced.
 - (c) In the event that bag failure has been observed:
 - (1) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
 - (2) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouses (DC48-03 and DC48-04) for the woodworking operation must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-7 (Part 70).

Conclusion

The operation of this wood furniture and fiberglass panel manufacturing plant shall be subject to the conditions of the attached proposed Minor Source Modification No. 039-15249-00087.

Appendix A: Process Particulate Emissions

Company Name: Monaco Coach Corporation
Address City IN Zip: 1205 East Lincoln Street, Nappanee, Indiana 46550
Minor Source Modification No.: 039-15249
Plt ID: 039-00087
Reviewer: Trish Earls/EVP
Date Application Received: December 3, 2002

State Potential Emissions (tons/year)						
A. Baghouses						
Process	No. of Units	Grain Loading per Actual Cubic Foot of Outlet Air	Air to Cloth Ratio Air Flow (acfm/ft ²)	Total Filter Area (ft ²)	Control Efficiency	Total (tons/yr)
DC48-03	1	0.01000	10.7	2,100	99.00%	843.59
DC48-04	1	0.01000	11.5	1,161	99.00%	501.25
Total Emissions Based on Rated Capacity at 8,760 Hours/Year						1344.84
Federal Potential Emissions (tons/year)						
A. Baghouses						
Process	No. of Units	Grain Loading per Actual Cubic Foot of Outlet Air	Air to Cloth Ratio Air Flow (acfm/ft ²)	Total Filter Area (ft ²)	Control Efficiency	Total (tons/yr)
DC48-03	1	0.01000	10.7	2,100	99.00%	8.44
DC48-04	1	0.01000	11.5	1,161	99.00%	5.01
Total Emissions Based on Rated Capacity at 8,760 Hours/Year and source controls						13.45

Methodology:State Potential (uncontrolled):

Baghouse (tons/yr) = No. Units * Loading (grains/acf) * Air/Cloth Ratio (acfm/ft²) * Filter Area (ft²) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

ESP (tons/yr) = No. Units * Loading (grains/acf) * Face Velocity (ft/sec) * Surface Area (ft²) * 1 lb/7,000 grains * 60 sec/min * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

Scrubber (tons/yr) = No. Units * Loading (grains/acf) * Flow Rate (gpm) * 1/Liquid to Air Ratio (gpm/1,000 acfm) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

Federal Potential (controlled):

Baghouse (tons/yr) = No. Units * Loading (grains/acf) * Air/Cloth Ratio (acfm/ft²) * Filter Area (ft²) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

ESP (tons/yr) = No. Units * Loading (grains/acf) * Face Velocity (ft/sec) * Surface Area (ft²) * 1 lb/7,000 grains * 60 sec/min * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)

Scrubber (tons/yr) = No. Units * Loading (grains/acf) * Flow Rate (gpm) * 1/Liquid to Air Ratio (gpm/1,000 acfm) * 1 lb/7,000 grains * 60 min/hr * 8760 hr/yr * 1 ton/2,000 lbs * 1/(1-Control Efficiency)